QINGDAO SANHUAN COLORCHEM CO., LTD.

17 FLOOR, YUHENG BUILDING, NO.170 XUZHOU NORTH ROAD, QINGDAO, CHINA
TEL:0086 532 88978177/88978188
FAX:0086 532 88962988/88967877
EMAIL: michael@cncolorchem.com
WEBSITE: www.cncolorchem.com

MATERIAL SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Fluorescent Pigment SHX Series

Manufacturer Identification:

QINGDAO SANHUAN COLORCHEM CO., LTD.
17 FLOOR, YUHENG BUILDING, NO.170 XUZHOU NORTH ROAD, QINGDAO, CHINA
Tel: +86-532-88978177/88978188
Fax: +86-532-88962988
Email:michael@cncolorchem.com

Section 2 - COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient	Content%	Hazardous
Sulphonamide-Melamine Resin	98	No
Dyestuff	2	No

Section 3 - HAZARDS IDENTIFICATION

Information concerning particular hazards for human and environment:
No hazardous to Human & Environment according to GHS Hazard classification

Section 4 - FIRST AID MEASURES

Health Effects – Acute:
Swallowed
No adverse effects known. It is considered to be non-toxic.
Eye
It is considered to be non-toxic. Can cause irritation.
Skin
It is considered to be non-toxic. Can cause irritation.
Inhaled
No adverse effects known. It is considered to be non-toxic.
Health Effects – Chronic:
No data available
Swallowed
Induce vomiting. Give water to drink. Call a physician.
Eye
Flush with water for 15 minutes. Call a physician.
Skin
Wash with soap and water.
Inhaled
Remove to fresh air. Treat symptoms.
First Aid Facilities

17 FLOOR, YUHENG BUILDING, NO.170 XUZHOU NORTH ROAD, QINGDAO, CHINA
EMAIL: michael@cncolorchem.com
TEL:0086 532 88978177/88978188
FAX:0086 532 88962988/88967877
WEBSITE: www.cncolorchem.com

Ensure an eye bath and safety shower are available and ready for use.

Section 5 - FIRE FIGHTING MEASURES

Fire / Explosion

Product is stable. Non reactive. Avoid high temperatures and strong oxidizers. In the event ofcombustion, carbon monoxide and/or carbon dioxide will be formed.

Extinguishing Media

Fire-fighters should wear full protective clothing including self-contained breathing apparatus.

In case of fire use equipment/media suitable for surrounding fire conditions.

Section 6 - ACCIDENTAL RELEASE MEASURES

Spills

Clean-up personnel should wear protective clothing. Prevent material from entering drains,sewers and other water courses.

Sweep up with sand or other absorbing material and hold for waste disposal.

Disposal

Dispose of in accordance with all Local, State and Federal regulations at an approved waste disposal facility.

Section 7 - HANDLING AND STORAGE

Ensure adequate ventilation maintain exposure levels below applicable workplace standards. Keep packaging well closed. Avoid storage temperatures < 0 deg C and > 30 deg C.

Flammability

Product is difficult to ignite unless directly involved in a flame. Product does not burn unless all the water is boiled away. Remaining organics may be ignitable.

Section 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear safety glasses or goggles, closed clothing, gloves and a respirator when generating mist.

Wash hands and face thoroughly after handling and before work breaks, eating, drinking,smoking and using toilet facilities.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: powder
Color: various
Formula : mixture
Tinting Strength: ≥95%
Soap Fastness: 3-4 class
Sunlight Fastness: 2-3 class
Thermal Resistance: ≥130℃
Softening poing: 125℃-145℃
Average Particle Size: ≤6um

17 FLOOR, YUHENG BUILDING, NO.170 XUZHOU NORTH ROAD, QINGDAO, CHINA
EMAIL: michael@cncolorchem.com
TEL:0086 532 88978177/88978188
FAX:0086 532 88962988/88967877
WEBSITE: www.cncolorchem.com

Boiling Point : N
Bulk density: 0.6 g/cm 3
Bulking value 1.6 cm 3 /g
Hegman grind ⩾5
Flash Point : N/A
PH : 5 ~ 7
Solubility in water : N/A g/l (25 deg C)
Oil absorption ⩽55%
Flammability Limits (as percentage volume in air)

Section 10 - STABILITY AND REACTIVITY

Thermal decomposition/conditions to be avoided
Stability,
Strong oxidizer, strong acid, and strong base not allowed.
Avoid the moist environment

Section 11 - TOXICOLOGICAL INFORMATION

Ensure adequate ventilation maintain exposure levels below applicable workplace standards.

Section 12 - ECOLOGICAL INFORMATION

N/M

Section 13 - DISPOSAL CONSIDERATIONS

Product:
Recommendation
Hand over to hazardous waste disposers. Dispose in accordance with federal, state and local regulation
Uncleaned packing:
Recommendation:
Empty contaminated packing thoroughly. They may be recycled after thorough and proper cleaning.

Section 14 - TRANSPORT INFORMATION

UN No. N/A
Class None Allocated
Sub Risk None Allocated
Hazchem Code N/A
Pack Group 0
EPG No. N/A
Shipping Name: FV Series Daylight Fluorescent Pigment
Package: packed in composite paper bag lined with PE film, net weight 25 kg.
The product dose not constitute a hazardous substance in national/ international road, rail, sea and air transport.

Section 15 - REGULATORY INFORMATION

17 FLOOR, YUHENG BUILDING, NO.170
XUZHOU NORTH ROAD, QINGDAO, CHINA
EMAIL: michael@cncolorchem.com
TEL:0086 532 88978177/88978188
FAX:0086 532 88962988/88967877
WEBSITE: www.cncolorchem.com

This product does not belong to the 6.1 toxic chemicals.

Section 16 - ADDITIONAL INFORMATION

To the best of our knowledge, the information contained herein is accurate. However producer nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.